

## The easy route to a big finish!

The SEAL® Image® 62 Plus Laminator offers new operators an uncomplicated approach to post-print finishing. Designed to be user-friendly, the SEAL Image 62 Plus is ideal for mounting, laminating and encapsulating images up to 61 inches in width.


Its versatile temperature range accommodates both low temperature, heat-activated films - such as SEAL® Print Guard® for inkjet prints - and higher temperature films - such as SEAL® ThermaShield® for electrostatic images.

The SEAL Image 62 Plus is an excellent mid-range laminator that meets your post-print finishing needs without finishing your budget.


### As easy as 1, 2, 3...



*Touch-pad control with predefined settings for temperature, speed and substrate thickness.*



*Swing-out supply shafts with unique auto-grip for easy loading and positioning of materials.*



*Optional roll-to-roll.*



### Features

- Touch-pad control panel with pre-programmed temperature, speed and substrate settings
- Automatic front and rear take-up shafts for release liner removal
- A swing-out, in-feed table that makes material loading fast and easy
- Swing-out supply shafts with auto-grip for easy loading and positioning of materials
- Silicone rollers for effortless cleaning
- Simple film tension adjustment
- L.E.D. setting indicators
- Roll-to-roll operation (optional)
- Temperature settings: 122°F (50°C), 203°F (95°C) and 248°F (120°C)
- Built-in cooling fans to cool film for a smooth film surface during heat-sealing applications
- Pull rollers that insure consistent film tension for a flat, even finish
- Accurate electric temperature control for even heating
- Sturdy, stand-alone design with built-in casters and leveling feet
- Quiet motor operation
- Anti-static pull roller that eliminates static build-up
- Foot control for hands-free operation
- Extensive safety system with emergency stops, electric eyes and a flashing light/buzzer proximity alarm
- Meets International Safety requirements

# SEAL® Image® 62 Plus Laminator

## SPECIFICATIONS

Specifications	Image® 62 Plus
Maximum Working Width	62" (1,575 mm)
Maximum Speed	6 feet per minute (1.8 m/min.)
Maximum Roller Opening	1" (25 mm)
Maximum Roller Temperature	250°F (120°C)
Dimensions	Width: 86.6" (2,200 mm) Depth: 24.8" (762 mm) (excluding tables) Height: 48" (1,220 mm)
Net Weight	1,153 lbs (530 kg)
Shipping Weight	1,263 lbs (580 kg)
Electrical Requirements	3N/PE-200 – 250 VAC, 50/60Hz, 25 A 1N/PE-200 – 250 VAC, 50/60Hz, 32 A
Maximum Power Consumption	7,000 Watts
Warranty	1 year parts (excluding rollers-180 days), 180 days labor

Note: It is recommended that your main power be installed by a licensed electrician in accordance with electrical codes in your area. Specifications subject to change without notice.

SEAL® Brands, Image®, Print Guard® and ThermaShield® are registered trademarks of SEAL Graphics Corporation.

**Neschen Americas**  
7091 Troy Hill Drive  
Elkridge, MD 21075  
Tel: 410-540-8900  
Fax: 410-579-8960

**Neschen Americas Canada**  
1601 Matheson Blvd. E.  
Mississauga, Ontario  
Canada, L4W 1H9  
Tel: 905-212-9232  
Fax: 905-212-9313



[www.sealgraphics.com](http://www.sealgraphics.com)

Contact your local distributor:

Neschen Americas recommends HP Designjet Printing Systems

©2006 Neschen Americas  
03-06